

WARRANTY CERTIFICATE

SharkBite NEXUS

Place and Date

for SharkBite NEXUS system in Plumbing and Heating installations Building owner: Project name: Installation company: Installation completed on: Installation launched in: The installation company confirms that the indicated project has been installed and put into operation with SharkBite NEXUS system of RWC EUROPE, being installed and commissioned according to the instructions of RWC, as well as to the assembly instructions and technical documentation of RWC EUROPE. Installation Company Place and Date

RELIANCE WORLDWIDE CORPORATION EUROPE S.L.

Warranty Certificate number (*):

Date, signature and stamp:

(*) to be filled in by RWC EUROPE

Signature & stamp

RWC's Distributor

Signature & stamp



RELIANCE WORLDWIDE CORPORATION EUROPE S.L. Autovía A92 km 209 - 18370 Moraleda Zafayona Granada (Spain)
Tel. +34 958 49 70 00
info.europe@rwc.com
www.rwc.com

OP-023/03-EN

RWC EUROPE assumes the warranty against the installation company, as long as the owner enforces his rights.

This warranty statement is valid only if it has been duly completed and signed and after the **RWC EUROPE** office has assigned the corresponding warranty certificate number.

To be ratified by **RWC EUROPE**, this declaration must be sent by email within three months after the installation's launch to **RWC EUROPE** via email: info.europe@rwc.com

This limited warranty shall expire in: **Ten (10) years** from the launch of the installation, **RWC EUROPE** takes responsibility up to a maximum amount of **Twenty Five million US Dollar - \$ 25.000.000 per claim.**

RWC EUROPE must receive written notice of the claim within warranty period and within ten (10) days of the incident.

Emergency repairs that may be performed by the owners or the installer without the corresponding written notice to **RWC EUROPE**, will not imply recognition of liability on the part of **RWC EUROPE**. **RWC EUROPE** should be provided with any materials or documents on possible causes, including affected fittings and pipes. In the case of pipes, samples must show all original marking. In the case of accessories, protective bags will be provided if possible.

RWC EUROPE will repair or replace any pipe or accessories that have proven defective.

SCOPE OF WARRANTY

We warrant that **SharkBite NEXUS** are produced in accordance with ISO 9001:2015 Quality Management procedures and are manufactured according to ISO 15875 - ISO 21003 and ISO 22391

RWC EUROPE guarantees the quality of its products free from manufacturing defects during the warranty period.

In addition, if the product is found to be defective due to a manufacturing defect, **RWC EUROPE** assumes the warranty and responsibility for a period of 10 years from the launch of the installation.

RWC EUROPE shall activate this warranty if the project owner claims against the installation company for direct damages suffered or incurred as a result of a defective product.

Any claim made during the warranty period shall not extend the general period of coverage.

Any warranty claim made during the warranty period shall not extend the overall period of warranty coverage.

CONDITIONS

The guarantee is assumed under the condition that no more than 10 years elapse between the launch of the installation and the accident.

Apart from this, the guarantee is valid only if the guarantee certificate and pressure test protocols duly completed and signed have been sent to **RWC EUROPE** within the maximum period of 3 months from the launch of the installation.

The warranty does not cover products not manufactured by **RWC EUROPE** except those authorized and agreed by **RWC EUROPE** in writing.

The warranty has no effect if the installation has not been carried out in accordance with the instructions for use of **RWC EUROPE** and according to the technical documentation.

The installation must have been carried out by a specialized and authorized company. The guarantee excludes damages caused by external factors (perforated pipes, frost damage, etc.), as well as errors or installation defects caused by the installer.

If possible damage is detected, it must be offered to **RWC EUROPE** in a maximum of 8 days from the accident and always before commencing repair actions.

If this is omitted, the guarantee will be void.

The interim measures taken by **RWC EUROPE** to minimize damage does not imply recognition of liability.

RWC Europe's responsibility covers the cost-free replacement of products manufactured by RWC Europe that are damaged and could be attributed to manufacturing defects.

RWC EUROPE assumes damage caused by accessing defective fittings or piping. Repair work necessary to restore the condition before the accident is also covered.

Compensation is excluded for the inability to use or loss of production, the stoppage of exploitation, depreciation and other indirect damages.

In order to enforce the rights covered by this warranty, the holder must present the certificate of guarantee duly completed.

RWC EUROPE reserves the right to order repair or rehabilitation actions from specialized companies of their choice.

The use of the guarantee during the validity period does not imply extension of the warranty. Any verbal agreements are not valid.

CLAIM PROCEDURE

Contact your **RWC EUROPE** distributor or the **RWC EUROPE** local sales office where you purchased the product, to begin the claim procedure.



PRESSURE TEST PROTOCOL FOR COLD & HOT WATER PLUMBING, RADIATOR HEATING and FAN COILS APPLICATIONS

PRESSURE TEST INSTRUCTIONS (Water)

	,						
Location of the installa	tion:						
Proyect's name:							
Application:	Plumbing	F	Radiator Heating F	an Coils			
	ther (indicate which)						
TEST							
Fill the installation with w	vater to build up pressure	at 3 bar during	1 hour and visually verify that the	re are no leaks.			
Increase the pressure to	15 bar during the next 2	4 hours.					
			normal to have pressure drops of				
sepending on the number	er of joints installed. For th	ils reason, it sno	ould be checked visually at low an	a nign pressure.			
INSTALLED SYS	STEM						
Pipe:	Commercial Brand						
Fitting:	Commercial Brand						
Diameters:	Ø 16						
Person in charge:							
Date of the test:	Froi	m (hh:mm):	Until (hh:mm):				
nstaller company nam	e:						
Legal address of the in	stallation company:						
Pressure test:	3 bar during 1 hou	r	Water leaks ? - YES	NO (
Pressure test:	15 bar during 24 hours		Water leaks ? - YES	NO 🔵			
Loss of pressure at the	e end of the test:	bar					
Final result of the test:		ок 🦳	NOT OK				
		CAUTION					
Installer company Signature & Stamp	,	If the ambient	temperature is below 0° C with po	ossibility of freezina.			
,		we do not recommend performing the pressure test with water. In this case it will be necessary to perform the test with					
			nt will be necessary to pen Air (see the next page).	om the test with			

OP-023/03-EN



Signature & Stamp

PRESSURE TEST PROTOCOL FOR COLD & HOT WATER PLUMBING, RADIATOR HEATING and FAN COILS **APPLICATIONS**

PRESSURE TEST INSTRUCTIONS (Air)

	,			,			
Location of the installa	ıtion:						
Proyect's name:							
Application:	Plumbing		Radiator Heating	Fan Coils			
О	ther (indicate which)						
TEST							
Fill the installation with a	air to build up pressure	at 0,5 bar during	2 hours.				
Increase the air pressure		_					
·	Ü						
INSTALLED SYS	STEM						
Pipe:	Commercial Brand						
Fitting:	Commercial Brand						
Diameters:	Ø 16 Ø 20 Ø 25 Ø 32						
CONFIRMATION Person in charge:							
Date of the test:	From (hh:mm): until (hh:mm):						
Installer company nam	le:		`				
Legal address of the in	stallation company:						
Pressure test:	0,5 bar during 2 ho	ours	Loss of pressure - YES	***************************************			
Pressure test:	3 bar during 10	min	Loss of pressure - YES	NO O			
Final result of the test:		ок	NOT OK				
Installer company		CAUTION					

The compressor equipment must guarantee that the pressure indicated in the test is not exceeded. If the use of compressed air is not controlled, there is a risk of bursting the operation of air compression.

The manometer used must have an accuracy of 1 mbar.

OP-023/03-EN