

CUT
PUSH
DONE



The SharkBite Plumbing System

SharkBite has established a reputation as one of Australia's best plumbing systems.



- Quick & easy to use.
- Fittings for PEX and Copper Pipe
- Conversion Fittings / other pipe systems.
- Assemble by hand, no costly tools.
- For use on hot and cold water.
- Approved for behind walls and in ground.
- Can be disconnected and reconnected.
- Australian made and owned.
- 25 year warranty.



Quick and Easy

SharkBite is quick and easy to install, making it the most time efficient plumbing system available, allowing the installer to move onto the next job faster than ever before.

Utilizing state of the art push-to-connect design DR brass fittings, the SharkBite system is easily assembled by hand.

Versatile & Re-usable

- Can be disconnected and reconnected with SharkBite disconnect clip or tongs
- Fittings can be rotated, allowing for easier installation in confined spaces. This feature is particularly useful where repairs and maintenance are required.

Conversion Fittings

- Copper to SharkBite PEX
- Polybutylene to SharkBite PEX
- PN20 PEX to SharkBite PEX
- Auspex PEX to SharkBite PEX

All your conversion requirements without the use of Tools.

Easily switch between any Pipe to SharkBite, quickly and conveniently.

Available in Couplings and Tee's.



New Products

Pipe Decoiler

Compact and folds down for easy transportation.

One user operation, reducing installation time.



Available Now

Mustard Pipe

100mtr Coils 1/2 & 3/4"



Available Now

PEX Fittings

F336 - Top-plated Extended Elbow

F356 - 20mm OD Back-plated Elbow

F358 - 20mm OD Back-plated Elbow



Available Now

Copper Push Fittings

For copper systems, use SharkBite Copper Fittings. A range of fittings and conversion adaptors are available. Copper fitting ends have a black collar.



Installation – Copper Pipe



Step 1 - Cut:

Using a Pipe Cutter, cut the copper tube to length making sure the pipe is cut squarely.



Step 2 - Deburr:

Remove burrs from the pipe using the SharkBite Deburr and Depth Gauge.



Step 3 - Mark:

Mark the pipe with a Safe Seal Indication Mark.



Step 4 - Push:

Insert the pipe by pushing firmly with a positive “click”. Ensure the Safe Seal Indicator Mark aligns with the release collar.

Step 5 - Done!



Step 6 - Disconnect:

Place non-branded face of the SharkBite disconnect on the release collar. Push against the collar and pull the pipe with a twisting action to release.

Installation per AS3500

PEX Product Range



- Used to connect SharkBite PEX Pipe
- PEX fittings have Mustard coloured ends.
- Fittings are rotatable after connection.
- Fittings can be installed on wet pipe even with water flowing.
- Fittings can be disconnected and reconnected as required.

Installation – PEX Pipe



Step 1 - Cut:

Using SharkBite PEX Pipe Cutters, cut the pipe squarely between two of the “SHARKBITE” Safe Seal Indicator Marks as shown in the picture.



Step 2 - Push:

Insert the pipe through the release collar to rest against the grab ring. Push the pipe firmly with a twisting action and push to the “SHARKBITE” Safe Seal Indicator Mark.



Step 3 - Done:

Ensure the “SHARKBITE” Safe Seal Indicator Mark aligns with the release collar as shown.



Step 4 - Disconnect:

Place non-branded face of the SharkBite disconnect on the release collar. Push against the collar and pull the pipe with a twisting action to release.

Installation per AS3500

Standards Approved

SharkBite fittings and PEX pipe comply with and are approved to Australian Standards AS2537 and AS2492-1994 respectively.

Australian Made & Owned

SharkBite fittings and pipe are manufactured in Australia in Reliance Worldwide Corporation (Aust.) Pty. Ltd. state of the art facilities. Stringent quality control and advanced manufacturing procedures guarantee product satisfaction.

25 Year Warranty

The SharkBite range of fittings and PEX pipe can be relied upon to perform year after year. SharkBite is backed by Reliance Worldwide Corporation's 25-year warranty.



Want more information?

Call our national customer service
hotline

1800 810 803

visit

www.sharkbite.com.au

or follow us on Facebook

facebook.com/SharkBiteAustralia



Download a QR code reader on your smartphone
and scan this to go to the SharkBite website.



PEX Fittings

Use SharkBite 25mm PEX Connections for DN25Cu

F1 Straight Coupling F008 16mm OD x 16mm OD F016 20mm OD x 20mm OD F020 25mm OD (DN25Cu) x 25mm OD (DN25Cu)	F1R Reducing Coupling F058 20mm OD x 16mm OD F060 25mm OD (DN25Cu) x 20mm OD	F2 Straight Female Connector F068 16mm OD x 20FI F072 16mm OD x 15FI F088 20mm OD x 20FI F094 25mm OD (DN25Cu) x 25FI	F3 Straight Male Connector F116 16mm OD x 20MI F120 16mm OD x 15MI F134 20mm OD x 20MI F138 20mm OD x 15MI F140 25mm OD (DN25Cu) x 25MI F142 25mm OD (DN25Cu) x 20MI	F12 Elbow F248 16mm OD x 16mm OD F256 20mm OD x 20mm OD F260 25mm OD (DN25Cu) x 25mm OD (DN25Cu)	F13 Male Elbow F280 16mm OD x 15MI	F14 Female Elbow F308 16mm OD x 15FI	
F15BP Backplate Female Elbow F334 16mm OD x 15FI F340 20mm OD x 20FI	F19BP Backplate Male Elbow F350 16mm OD x 15MI x 75mm F351 16mm OD x 15MI x 185mm F352 16mm OD x 15MI x 100mm F354 20mm OD x 20MI x 185mm F356 20mm OD x 15MI x 100mm F358 20mm OD x 15MI x 200mm	Top-Plated Male Elbow F336 16mm OD x 15MI x 100mm	F24 Equal Tee F362 16mm OD x 16mm OD x 16mm OD F370 20mm OD x 20mm OD x 20mm OD F374 25mm OD (DN25Cu) x 25mm OD (DN25Cu) x 25mm OD (DN25Cu)	F25, F26, F27 Unequal Tee F412 20mm OD x 20mm OD x 16mm OD F416 25mm OD (DN25Cu) x 25mm OD (DN25Cu) x 20mm OD F444 20mm OD x 16mm OD x 20mm OD F454 20mm OD x 16mm OD x 16mm OD	F61 Stop End F514 16mm OD F518 20mm OD F520 25mm OD (DN25Cu)	F62 Straight Tap Connector F526 16mm OD x 15FI Nut F530 20mm OD x 20FI Nut	
F63 Bent Tap Connector F532 16mm OD x 15FI F536 20mm OD x 20FI	PE-X Tail Reducer F720 16mm OD Tail x 20 OD Tail F722 16mm OD Tail x 25 OD Tail F724 20mm OD Tail x 25 OD Tail	PE-X Tail / Capillary Tail F608 16mm OD Tail x 15 Cap Tail F609 20mm OD Tail x 20 Cap Tail	PE-X Tail / Copper Adaptor F600 16mm OD Tail x 15 Cu F602 16mm OD Tail x 20 Cu F604 20mm OD Tail x 15 Cu F606 20mm OD Tail x 20 Cu	PE-X Tail / Male Adaptor F740 16mm OD x 15MI F744 20mm OD x 15MI F746 20mm OD x 20MI F750 25mm OD x 20MI	PE-X Tail / Female Adaptor F760 16mm OD Tail x 15 FI F764 20mm OD Tail x 15 FI F766 20mm OD Tail x 20 FI F770 25mm OD Tail x 20 FI	PE-X Tail Plug F755 16mm OD Tail F756 20mm OD Tail F757 25mm OD Tail	PE-X / Flare Adaptor F610 16mm OD x 15 Flare F612 20mm OD x 20 Flare
Recessed - Right Angled Breech F630 300mm F632 200mm	Recessed - Straight Breech F640 300mm F642 200mm	Shower - Right Angled Breech F650 200mm F652 150mm	Shower - Right Angled Breech F655 200mm Inverted F657 150mm Inverted	Shower/Bath - Right Angled Breech F660 200mm F662 300mm	Ball Valves BVF670 16mm OD x 16mm OD BVF672 20mm OD x 20mm OD BVF674 25mm OD (DN25Cu) x 25mm OD (DN25Cu) BVF680 16mm OD x 15FI BVF682 20mm OD x 20FI BVF684 25mm OD x 25FI (DN25Cu)	Manifolds F690-3S DN20Cu x 3 Way 16mm PEX Take Offs x Stop End F690-3T DN20Cu x 3 Way 16mm PEX Take Offs x DN20Cu F690-4S DN20Cu x 4 Way 16mm PEX Take Offs x Stop End F690-4T DN20Cu x 4 Way 16mm PEX Take Offs x DN20Cu	

Tempering Valves



Insulated Tempering Valves (TV) with SharkBite Fittings

MIXF110091	16mm Pex Insulated Standard TV
MIXF110121	20mm Pex Insulated Standard TV
MIXF111161	16mm Pex Insulated Ultra Solar TV
MIXF111171	20mm Pex Insulated Ultra Solar TV
MIXRA110091	15mm Copper Insulated Standard TV
MIXRA111161	15mm Copper Insulated Ultra Solar TV

Conversion Fittings

Conversion Coupling

F009	16mm OD x DN15 Cu
F017	20mm OD x DN20 Cu
F009PX	16mm OD x 16mm PN20
F017PX	20mm OD x 20mm PN20
F009PB	16mm OD x 16mm Polybutylene
F017PB	20mm OD x 22mm Polybutylene
F009AP	16mm OD to 16mm Auspex Coupling
F017AP	20mm OD to 20mm Auspex Coupling
F017AP	25mm OD (DN25Cu) x DN20

Conversion Elbow

F250	16mm OD x DN15 Cu
F258	20mm OD x DN20 Cu

Conversion Tee

F363	16mm OD x 16mm OD x DN15 Cu
F364	DN15 Cu x DN15 Cu x 16mm OD
F371	20mm OD x 20mm OD x DN20 Cu
F372	DN20 Cu x DN20 Cu x 20mm OD
F364PX	16mm PN20 x 16mm PN20 x 16mm
F372PX	20mm PN20 x 20mm PN20 x 20mm
F364PB	16mm Poly/But x 16mm Poly/But x 16mm
F372PB	20mm Poly/But x 20mm Poly/But x 20mm
F417	25mm OD (DN25Cu) x 25mm OD (DN25Cu) x DN20

Pipe

Potable Water

F860	16mm OD 5m Straight
F864	16mm OD 50m Coil
F864100	16mm OD 100m Coil
F870	20mm OD 5m Straight
F874R	20mm OD Red 50m Coil
F880R	25mm OD Red 5m Straight
F882R	25mm OD Red 25m Coil
F874100	20mm OD 100m Coil

Hot Water

F860R	16mm OD Red 5m Straight
F864R	16mm OD Red 50m Coil
F870R	20mm OD Red 5m Straight
F874R	20mm OD Red 50m Coil
F880R	25mm OD Red 5m Straight
F882R	25mm OD Red 25m Coil

Recycled Water

F862L	16mm OD Lilac 25m Coil
F872L	20mm OD Lilac 25m Coil
F882L	25mm OD Lilac 25m Coil

Rain Water

F860G	16mm OD Green 5m Straight
F862G	16mm OD Green 25m Coil
F870G	20mm OD Green 5m Straight
F872G	20mm OD Green 25m Coil
F880G	25mm OD Green 5m Straight
F882G	25mm OD Green 25m Coil

Pre Conduited

F863	16mm OD 25m Co
F873	20mm OD 25m Co

Oxygen Barrier

F866H	16mm EVOH PEX x 100m
F876H	20mm EVOH PEX x 100m
F886H	25mm EVOH PEX x 100m

Foam Pipe Insulation

F862RR3	25m x 16mm Preinsulated PEX R.O.3
F872RR3	25m x 20mm Preinsulated PEX R.O.3
F882RR3	25m x 25mm Preinsulated PEX R.O.3
F862RR8	25m x 16mm Preinsulated PEX R.O.8
F872RR8	25m x 20mm Preinsulated PEX R.O.8
F882RR8	25m x 25mm Preinsulated PEX R.O.8

Copper Fittings

Use SharkBite 25mm PEX Connections for DN25Cu

No1 Straight Coupling RA008 DN15 RA016 DN20	No1R Reducing Coupling RA058 DN20 x DN15 F061 DN25 (25mm OD) x DN20	No2 Female Connector RA072 DN15 x 15mm FI RA088 DN20 x 20mm FI	No3 Male Connector RA120 DN15 x 15mm MI RA134 DN20 x 20mm MI	Hot Water Elbow RA380 DN15 x 20mm MI	No12 Elbow RA248 DN15 RA256 DN20
No15BP Female Lugged Elbow RA334 DN15 x 15mm FI RA340 DN20 x 20mm FI	No19BP Male Lugged Elbow RA350 DN15 x 15mm MI 75mm Long RA351 DN15 x 15mm MI 185mm Long RA352 DN15 x 15mm MI 100mm Long	No24 Tee RA362 DN15 RA370 DN20	No25 Unequal Tee RA412 DN20 x DN20 x DN15 RA454 DN20 x DN15 x DN15 F417 DN25 (25mm OD) x DN25 (25mm OD) x DN20	No61 Stop End RA514 DN15 RA518 DN20	
Slip Coupling RA3008 DN15 RA3016 DN20 RA3020 DN25	Tail x Male Adaptor RA740 15mm MI x DN15 RA746 20mm MI x DN20	Tail x Female Adaptor RA760 15mm FI x DN15 RA766 20mm FI x DN20	Flared Compression Adaptor RA610 DN15 x DN15 Flare RA612 DN20 x DN20 Flare	SharkBite Tail x OD Reducer RA720 DN15 x DN20 Tail RA722 DN15 x DN25 Tail RA724 DN20 x DN25 Tail	Ball Valves BVRA670 DN15 x DN15 BVRA672 DN20 x DN20 BVRA680 DN15 x 15mm FI BVRA682 DN20 x 20mm FI

Tools & Accessories

Tube Clips

F820	16mm OD Timber Nail
F830	20mm OD Timber Nail
F850	25mm OD Timber Nail
F822	16mm OD Masonry Nail
F832	20mm OD Masonry Nail
F852	25mm OD Masonry Nail
F824	16mm OD Tek Screw
F834	20mm OD Tek Screw
F854	25mm OD Tek Screw
F826	16mm OD Concrete Anchor
F836	20mm OD Concrete Anchor
F828	16mm OD Metal Stud
F838	20mm OD Metal Stud

Tube Bend Support

F840	16mm
F842	20mm

Disassembly Clips

F710	16mm OD
F712	20mm OD and DN20Cu
RA710	DN15 DN15Cu

Disassembly Tongs

F711	16mm OD Yellow (PEX)
F713	20mm OD Green (PEX)
F715	25mm OD Chrome (PEX)
RA711	DN15 Red (copper)
RA713	DN20 White (copper)

Exact Packs

F4001	Starter Kit (Tools only)
-------	--------------------------

Deburrer & Depth Gauge

F702	DN15, DN20, DN25
------	------------------

Chasing Sleeve

F704	16mm OD & 20mm OD 200mm Flat Coil
------	-----------------------------------

Corrugated Sleeve

F706	23mm ID Black to suit 16mm OD & 20mm OD 25m Coil
F707	29mm ID Black to suit 25mm OD 25m Coil

Tube Cutter

F700	16mm OD to 25mm OD (Ratchet)
F701	16mm OD to 25mm OD

Pipe De-Coiler

UFH034	Pipe De-Coiler - suitable for 50 and 100m coils
--------	---

SharkBite Customer Service Australia Wide 1800 810 803

